



1 2 3 4 5 6 7 8

F
E
D
C
B
A

線路板开孔尺寸
P.C.B LAYOUT

SPECIFICATION
 1. Rating : DC 30V 0.5A;
 2. Contact resistance: $\leq 0.03\Omega$;
 3. Insulation resistance: $\geq 100M\Omega$ (DC250V);
 4. Withstand voltage: 500VAC ;
 5. Insertion and extraction forces: 3-30N;
 6. Life tests: 5,000 cycles;
 7. Marked Δ are important dimensions.

① ② ③ ④ ⑤ ⑥ ⑦ ⑧

1	HOUSING	1	FRF	FRF		
1	CONTACT FOOT	1	BRONZE T1.03mm	BRONZE T1.03mm		Au-Plating
1	CONTACT FOOT	1	BRONZE T1.03mm	BRONZE T1.03mm		Au-Plating
1	CONTACT FOOT	1	BRONZE T1.03mm	BRONZE T1.03mm		Au-Plating
1	CONTACT FOOT	1	BRONZE T1.03mm	BRONZE T1.03mm		Au-Plating
1	CONTACT FOOT	1	BRONZE T1.03mm	BRONZE T1.03mm		Au-Plating

SHENG CONG ELECTRONIC CO.,LTD

REV	DATE	BY	CHK	APP	REASON
0	13/09/26	JASON	Max.hu		

SHENG CONG ELECTRONIC CO.,LTD
 TITLE: P.C.B LAYOUT
 P.C.B NO: PJ-D8127K
 SHEET: 1 OF 1

Signature: Date: Appr: Rev: Jason: Max.hu: 13/09/26